

I. What is important when choosing the place where the container will be left?

- The place is flat and asphalted.
- The place is flat and gravelly.
- The place is flat and load-bearing.

II. The power take-off must be switched on when using a vehicle without a level lift to turn on/on the footrest.



YES / NO

III. In a vehicle with a level lift, there is no need to connect a hydraulic pump/PTO to turn on / on the footrest.

TRUE / FALSE

IV. What procedures should be performed before the footrest is removed?

- Put the gear in neutral and open the manual pallet castings.
- Put the gear in neutral, apply the parking brake and open the manual pallet locks.
- Put the gear in neutral, apply the parking brake and open all pallet locks.
- Put the gear in neutral, engage the PTO and open all pallet locks.

V. If a vehicle with a level lift has a tail lift, it must be opened before the footrest can be removed. What should be taken into account in this case?

- The tail lift is lowered enough to leave the magnetic switch behind the wishbone.
- The tail lift is lowered down enough.
- The tail lift is lowered enough to allow the vehicle to slide out from under the platform.

NOTES:

STEP IN to the online world/virtual learning, Facilitation of access to Vocational practice through online teaching at secondary technical schools

The project is co-financed by the European Union, ERASMUS+ programme.

Contract number: 2020-1-SK01-KA226-VET-094400

The European Commission's support for the production of this material does not constitute an endorsement of the contents, which reflect the views only of the authors, and the Commission cannot be held responsible for any use which may be made of the information contained therein.

STEP IN project in partnership with:

